

**What is Claimed is:**

Sub  
A25  
5 1. A digital processing system comprising a microprocessor,  
wherein the microprocessor is operable to perform a method for calling a  
subroutine, the method comprising the steps of:

branching to the subroutine by executing a first instruction to provide  
an address of the subroutine; and

calculating a return address by executing a second instruction to  
determine a relative return address.

10 2. The digital processing system of Claim 1, wherein the step of  
calculating a return address comprises the step of adding a relative  
displacement value provided by the second instruction to a program address  
value associated with the second instruction.

15 3. The digital processing system of Claim 2, wherein the step of  
calculating a return address further comprises the step of storing the return  
address in a general purpose register of the microprocessor.

20 4. The digital processing system of Claim 1, wherein the second  
instruction is executed during a delay slot associated with the first  
instruction.

25 5. The digital processing system of Claim 1, wherein the second  
instruction is executed before executing the first instruction.

6. The digital processing system of Claim 1, wherein during the  
step of calculating a return address, a plurality of second instructions are

A25  
conditionally executed in response to a predicate value such that the return address is responsive to the predicate value.

5 7. The digital processing system of Claim 1, wherein during the step of calculating a return address the return address is remotely associated with the second instruction.

10 8. The digital processing system of Claim 1, further comprising the step of filling a number of delay slots associated with the first instruction in an instruction execution pipeline of the microprocessor by executing a number of virtual no-operation (NOP) instructions specified by the second instruction.

15 9. A digital processing system comprising a microprocessor, wherein the microprocessor is operable to perform a method for forming a relative address, the method comprising the steps of:

fetching a sequence of instructions in response to address locations provided by a program counter;

20 executing a first instruction of the sequence of instructions by using a first address value provided by the program counter as a source operand.

25 10. The digital system of Claim 9, wherein the step of executing a first instruction comprises the step of combining a displacement value provided by the first instruction with the first address value provided by the program counter.

11. The digital system of Claim 10, wherein the step of executing the first instruction further comprises the step of providing a number of

A25  
virtual no-operation (NOP) instructions for execution after the step of  
executing the first instruction.

5 12. The digital system of Claim 10, wherein the microprocessor  
comprises:

an instruction execution pipeline having a plurality of stages;

the program counter being associated with a fetch stage of the  
instruction execution pipeline;

10 FIFO circuitry connected to receive address values from the program  
counter, the FIFO circuitry operable to delay each address value received  
from the program counter; and

15 a first functional circuit associated with an execution phase of the  
instruction execution pipeline connected to receive a delayed address value  
from the FIFO circuitry, wherein the first functional circuit is operable to add  
the displacement value provided by the first instruction to a first delayed  
address value provided by the program counter.

13. The digital system of Claim 12, further comprising:

20 a plurality of functional units associated with the execution phase the  
instruction execution pipeline;

wherein the instruction execution pipeline receives a fetch packet  
containing a plurality of instructions associated with each address value  
provided by the program counter;

25 wherein a dispatch stage of the pipeline is operable to provide an  
execution packet that spans two or more fetch packets; and

wherein the FIFO circuitry is operable to provide the first delayed  
address value such that the first delayed address value is associated with one  
of the two or more fetch packets in which an instruction executed by the first  
functional unit is located.

A25

14. The digital system according to Claim 9 being a cellular telephone, further comprising:

an integrated keyboard (12) connected to the microprocessor via a keyboard adapter;

5 a display (14), connected to the microprocessor via a display adapter;  
radio frequency (RF) circuitry (16) connected to the microprocessor;

and

an aerial (18) connected to the RF circuitry.

10 15. A method for calling a subroutine in a digital processing system comprising a microprocessor, the method comprising the steps of:

branching to the subroutine by executing a first instruction to provide an address of the subroutine; and

15 calculating a return address by executing a second instruction to determine a relative return address.

20 16. The method of Claim 15, wherein the step of calculating a return address comprises the step of adding a relative displacement value provided by the second instruction to a program address value associated with the second instruction.

25 17. The method of Claim 15, wherein the step of calculating a return address further comprises the step of storing the return address in a general purpose register of the microprocessor.

18. A method for forming a relative address in digital processing system comprising a microprocessor, the method comprising the steps of:

fetching a sequence of instructions in response to address locations provided by a program counter;

1725  
executing a first instruction of the sequence of instructions by using a first address value provided by the program counter as a source operand.

5 19. The method of Claim 18, wherein the step of executing a first instruction comprises the step of adding a displacement value provided by the first instruction to the first address value provided by the program counter.

10 20. The method of Claim 20, wherein the step of executing the first instruction further comprises the step providing a number of virtual no-operation (NOP) instructions for execution after the step of executing the first instruction.

15 21. A method for operating a compiler for a microprocessor, wherein the microprocessor is operable to execute a first type of instruction that performs a specified operation and also directs that a selectable number of virtual no-operation (NOP) instructions be executed after executing the first type instruction, the method comprising the steps of:

20 determining that a first instruction of the first type of instruction is to be executed in a delay slot of a first branch type instruction;

determining that a second instruction of a second type of instruction is to be executed in a delay slot of the first branch type instruction;

arranging an instruction sequence such that the first instruction is executed after the second instruction;

25 determining a remaining number of unused delay slots of the first branch type instruction; and

inserting a value in the first instruction to direct that a selectable number of virtual NOP instructions be executed after executing the first type instruction, wherein the selectable number of NOPs is the remaining number of unused delay slots of the first branch instruction.